


XtremeTrim® Vertical Siding H-Mold



EXTRUDED ALUMINUM

PRODUCT DETAIL:



ITEM ID	SIDING SIZE	LENGTH
SHM5168	5/16" (8mm)	8'
SHM51610	5/16" (8mm)	10'
SHM7168	7/16" (11mm)	8'
SHM71610	7/16" (11mm)	10'
SHM588	5/8" (16mm)	8'
SHM5810	5/8" (16mm)	10'
SHM110	1" (25.4mm)	10'

DESIGN FEATURES: Designed to cover vertical joints in siding. Longer lasting and more effective than contractor grade caulk. Provides a smooth seam at joints.

MATERIAL: 6063 T-5 .050" (1.27mm) ± .005 extruded aluminum alloy with proprietary coating that protects against harsh weather conditions and allows for paint adhesion.

FINISH: Unless specified all XtremeTrim® items are provided in primed finish. Also available in popular siding/soffit colors in standard face only color match or full coverage CoastalColorCoating™. Clear Anodized is stocked and custom anodized is available (minimums apply).

FASTENERS AND FASTENING: Stainless steel fasteners are recommended. XtremeTrim® profiles may be secured in place with a few SS nails until fastened through panels and into studs during panel or plank fastening per siding manufacturer's instructions.

CUTTING & PAINTING: Use a non-ferrous carbide miter saw blade when cutting XtremeTrim®. Use Direct To Metal (DTM) paint when jobsite painting. See painting guide.

XTREMETRIM® BUTT JOINT: Sealant is required between butt joints where two trims come together. May also be further protected by use of a piece of XtremeFlashing™ behind the butt joint or with a metal flasher behind the joint.

NOTE: Use of the XtremeTrim® Vertical Siding H-Mold at horizontal joints is not recommended.



RECOMMENDED APPLICATION NOTES:

Please follow siding manufacturer's best practice guides when installing. XtremeTrim® profiles DO NOT form a moisture management system. The architect and builder are responsible for designing and installing a code compliant building envelope. Before installing XtremeTrim® use either a drainable housewrap or a standard housewrap with a rainscreen system if required by code or siding manufacturer.

